



User Manual

Organisation: https://github.com/Hyperperform

Developers: Rohan Chhipa Avinash Singh Jason Gordon

Updated October 23, 2016

Client



MagnaBC http://www.magnabc.co.za/

Contents

Syst	tem Over	rview	3
Syst	tem Conf	figuration	3
2.1	Docker in	nstallation	. 3
2.2	Manual I	Installation	. 3
2.3	Event Ga	athering	. 4
2.4	Miscellan	neous	5
Inst	allation		6
3.1	Docker In	nstallation	. 6
3.2	Manual I	Installation	. 6
	3.2.1 W	/ildFly	. 6
	3.2.2 Pe	ostgreSQL	. 6
	3.2.3 A	$\operatorname{ctiveMQ}$. 9
3.3	Notificati	ions	. 10
	3.3.1 D	eploying to WildFly	. 12
	3.3.2 Fi	ront-end Dashboard	. 12
Get	ting Star	ted/Using the System	14
4.1	Logging 1	In	. 14
4.2	Your Das	shboard	. 15
	4.2.1 Fi	iltering Your Performance Score	. 16
4.3	Detailed	View	. 17
	4.3.1 G	raph View	. 17
	4.3.2 Ta	able View	. 18
4.4	Signing (Dut	. 19
4.5	Manageri	ial features	. 20
	4.5.1 M	Ianagerial view	. 20
	4.5.2 U	ser registration	21
	4.5.3 Fe	orecasting	. 24
4.6	Errors .		25
	Syst 2.1 2.2 2.3 2.4 Inst 3.1 3.2 3.3 Get 4.1 4.2 4.3 4.4 4.5 4.6	System Over System Configuration 2.1 Docker in 2.2 Manual I 2.3 Event Ga 2.4 Miscellar Installation 3.1 Docker In 3.2 Manual I 3.2.1 W 3.2.2 P 3.2.3 A 3.3 Notificat: 3.3.1 D 3.3.2 FI Getting Star 4.1 Logging I 4.2 Your Das 4.2.1 F 4.3 Detailed 4.3.1 G 4.3.2 T 4.4 Signing C 4.5 Manager 4.5.1 M 4.5.2 U 4.5.3 F 4.6 Errors	System Overview System Configuration 2.1 Docker installation 2.2 Manual Installation 2.3 Event Gathering 2.4 Miscellaneous 1 Docker Installation 3.1 Docker Installation 3.2 Manual Installation 3.2.1 WildFly 3.2.2 PostgreSQL 3.2.3 ActiveMQ 3.3.1 Deploying to WildFly 3.3.2 Front-end Dashboard 3.3.2 Front-end Dashboard 4.1 Logging In 4.2.1 Filtering Your Performance Score 4.3.1 Graph View 4.3.2 Table View 4.3.4 Signing Out 4.5.1 Managerial features 4.5.1 Managerial view 4.5.3 Forecasting 4.6 Errors

1 System Overview

Many different tools are available for measuring the quality of products made, but very few tools exist which assess the quality of the people making said products. People play a huge role in a project, and trying to monitor each and every one becomes a tedious task which diverts man power away from other more critical tasks. Whether it be for an end of year evaluation, or attempting to assess the current status of a project, generating a report on a staff member can help keep up productivity, as well as get them any help they need in order to resume quality performance. By ensuring that there is constant quality performance from each individual on a project, one can increase project quality as well as reduce project risks such as loss of an important team member during a critical stage of a project's life-cycle.

The HyperPerform system has the ability to automatically gather information from multiple integrations such as GitHub and Travis. This alleviates the responsibility of the manager and HR having to manually monitor each employee by filling in time sheets and performance documents. The system aims to simplify management by allowing a manager to view all relevant employee data in a simple and easy to understand manner. This data is represented in the form of a report. These reports can be a summarised report or a more detailed report on an employees' activities.

In order to allow the system to be used in many different environments, we have developed the system to be highly pluggable in nature, so that one could easily increase the number of integrations from which information can be pulled.

2 System Configuration

This guide has been created for users who are using a Linux based operating system. To install the HyperPerform system on the machine you will be required to have an active connection to the internet. Please note that high amounts of data might be consumed during this process.

2.1 Docker installation

To install the system with ease and to avoid all the system configurations you can download Docker to handle this for you. Docker can be found at www.docker.com where guides are made available for installing docker on a particular operating system. If you intend to use Docker to install the HyperPerform system then please ensure you install Docker on your machine.

2.2 Manual Installation

The manual installation requires you to download the source code from the GitHub repository. The newest release is highly recommended. To carry out a manual installation please ensure you have Maven and the WildFly application server on your machine.

Maven can be downloaded from: maven.apache.org

WildFly can be downloaded from: wildfly.org

Please ensure you download WildFly 10. The HyperPerform system was fully tested on this version of WildFly. Any other version might produce unexpected behaviour.

For the front-end Dashboard please ensure you have Nodejs (version 6.4.0 or higher) installed on your machine. Nodejs can be found at https://nodejs.org/en/.

2.3 Event Gathering

The system gathers information through webbook technology. Thus to be able to receive any events the computer on which the system will be installed **must** be connected to the internet. When configuring the integrations you will need to provide the URL for that integration to send events to. The following figure shows the GitHub webbook.

Webhooks / Manage webhook	
We'll send a POST request to the URL below with details of any subscribed events. You data format you'd like to receive (JSON, x-www-form-urlencoded, <i>etc</i>). More information developer documentation.	u can also specify which on can be found in <mark>our</mark>
Payload URL *	
https://github.hyperperform.me/	
Content type	
application/json	
Secret	
By default, we verify SSL certificates when delivering payloads.	Disable SSL verification
Which events would you like to trigger this webhook?	
Just the push event.	
Send me everything.	
Let me select individual events.	

Figure 1: Adding GitHub webhook

An optional feature would be to bind a domain name to the global IP address of the server. However this is merely for readability purposes and work affect system performance in any way.

2.4 Miscellaneous

Certain components of the system require user names which are consistent. The Git event processor is one such component. When using GitHub on your local machine please ensure that your local configurable Git name corresponds to your actual GitHub username.

To check your local Git name open terminal or command prompt and run the following command:

git config user.name

If the name corresponds to your account name then nothing further needs to be done and you can continue to the installation. However if the two names do not match then run the following command:

```
git config ---global user.name "<username>"
```

In the command above the <username> is your actual account name.

3 Installation

3.1 Docker Installation

Assuming you have docker installed on your machine, simply run the following command in terminal:

docker run hyperperform/HyperPerform

This will download the HyperPerform Docker image from DockerHub and run it on you machine.

The front end component does not have a Docker image at this point in time. To install the front end component please refer to section 3.2.5 for the manual installation.

3.2 Manual Installation

This installation guide assumes a Linux Server running Ubuntu 14 or higher:

3.2.1 WildFly

Once you have downloaded the WildFly application server please carry out the WildFly installations and add a user. Once this is done proceed to installing PostgreSQL.

3.2.2 PostgreSQL

The install PostgreSQL on your machine:

Install via terminal:

```
sudo apt-get update
sudo apt-get install postgresql postgresql-contrib
```

To configure PostgreSQL to connect remotely:

sudo nano /etc/postgresql/9.3/main/postgresql.conf

Edit the following lines:

```
listen_addresses = "*"
```

Create database hyperperform and the tables

Run the following commands in terminal:

psql -c 'CREATE DATABASE hyperperform;' -U postgres

- psql -d hyperperform -c 'CREATE TABLE public." GitPush" (id integer NOT NULL, repository character varying(255), " timestamp" timestamp without time zone, username character varying(255), commitsize integer, url character varying(255) , message character varying(255), CONSTRAINT "GitPush_pkey" PRIMARY KEY (id)); CREATE SEQUENCE public. hibernate_sequence INCREMENT 1 MINVALUE 1 MAXVALUE 9223372036854775807 START 1 CACHE 1; ' -U postgres
- psql -d hyperperform -c 'CREATE TABLE public." TravisEvent" (id integer NOT NULL, branch character varying(255), commiter character varying(255), repo character varying(255), status character varying(255), "timestamp" timestamp without time zone, CONSTRAINT "TravisEvent_pkey" PRIMARY KEY (id));' -U postgres

psql -d hyperperform -c 'CREATE TABLE public." CalendarProject" (projectid integer NOT NULL, calendarid character varying (255), collaborators bytea, creator character varying(255), duedate timestamp without time zone, eventid character varying(255), reponame character varying(255), "timestamp" timestamp without time zone, CONSTRAINT " CalendarProject_pkey" PRIMARY KEY (projectid)); '-U postgres

psql -d hyperperform -c 'CREATE TABLE public." CalendarMeeting" (meetingid integer NOT NULL, calendarid character varying (255), creator character varying(255), duedate timestamp without time zone, eventid character varying(255), location character varying(255), "timestamp" timestamp without time zone, CONSTRAINT "CalendarMeeting_pkey" PRIMARY KEY (meetingid)); ' -U postgres

psql –d hyperperform –c 'CREATE TABLE public."
$CalendarMeeting_attendees"$ ("CalendarMeeting_meetingID"
integer NOT NULL, attendees integer, attendees_key character
varying(255) NOT NULL, CONSTRAINT "
CalendarMeeting_attendees_pkey" PRIMARY KEY ("
$CalendarMeeting_meetingID$ ", attendees_key), CONSTRAINT
fkn4q1pmj9vx3tfsaw9irp9voax FOREIGN KEY ("
CalendarMeeting_meetingID") REFERENCES public."
Calendar Meeting" (meetingid) MATCH SIMPLE ON UPDATE NO
ACTION ON DELETE NO ACTION); '-U postgres

- psql -d hyperperform -c 'CREATE TABLE public." GitIssue"(id integer NOT NULL, action character varying(255), assignee character varying(255), createdby character varying(255), issueid bigint, repository character varying(255), " timestamp" timestamp without time zone, title character varying(255), url character varying(255), CONSTRAINT " GitIssue_pkey" PRIMARY KEY (id)); '-U postgres
- psql -d hyperperform -c 'CREATE TABLE public." User" (email character varying(255) NOT NULL, gitusername character varying(255), name character varying(255), "position" integer, profilepicture bytea, role integer, surname character varying(255), username character varying(255), password character varying(255), CONSTRAINT "User_pkey" PRIMARY KEY (email)); ' -U postgres
- psql -d hyperperform -c 'CREATE TABLE "AccessEvent"(id integer NOT NULL, email character varying(255), day bigint, deviceid character varying(255), employeeid character varying(255), name character varying(255), surname character varying(255), "timestamp" timestamp without time zone, CONSTRAINT " AccessEvent_pkey" PRIMARY KEY (id)); '-U postgres
- psql -d hyperperform -c 'CREATE TABLE public." ForecastData"(
 data character varying(10485760) NOT NULL, CONSTRAINT "
 ForecastData_pkey" PRIMARY KEY (data)); ' -U postgres

3.2.3 ActiveMQ

To setup ActiveMQ on your server:

- Start up your WildFly application server
- Navigate to WildFly management console on localhost:9990
- Navigate to configurations tab and click on sub-systems
- Scroll down and search for Messaging-ActiveMQ and click on it
- Click on default, select queues/topics

WildFly					Messages: 0 👗 avinash
Home Deployments Config	uration Runtime Access C	ontrol Patch	ning		
Configuration	Subsystem (31)	Me	ssaging Provider	Add	
Subsystems	>	de	fault	Queues/Topics 🔻	Messaging Provider
	10				A messaging provider represents an ActiveMQ server instance.
nterfaces	Logging				Queues / Topics
Socket Binding	- 685.15				Create queues and topics which are used by this messaging provider.
)-th-	Deployment Scanners				Connections
auto	JMX	- 1			Manage acceptors which define how and connections can be made to the messaging provider.
yacin roperces	Remoting				Create bridges, which consume messages from a source queue, and forward them to a target address, typically on a different server.
	Infinispan				Clustering
	Messaging - ActiveMQ	>			Define broadcast and discovery groups which control how connectors are handled and distributed by this provider.
	Security	>			Manage cluster connections to group servers into clusters so that messages ca be load balanced between the nodes of the cluster.
	Web Services				Provider settings
	Web/HTTP - Undertow	>			Fine tune the settings of this messaging provider.
10.0.0 Final					Tools & Settin

Figure 2: Subsystems Configuration

- Click add and input the following information:
 - Name*: hyperperform
 - JNDI Names*: java:/jms/queue/hyperperform

S	Create JMS Que	le	2	' ×
ii.			Need Help?	
s	Name *:	hyperperform		l
ŀ	JNDI Names *:	java:/jms/queue/hyperperform	h	l
		One item per line		l
ł	Durable?*:	Ø		
L	Selector:			•
L			Cancel Sav	е
				/

Figure 3: Queue Configuration

• Click save

3.3 Notifications

Please Note: These settings are for a Gmail configuration if you are running your own stmp server you need to adjust the information appropriately. To setup Notifications via Email on the server:

- Start up your WildFly application server
- Navigate to WildFly management console on localhost:9990
- Navigate to configurations tab and click on sub-systems
- Scroll down and search for Email and click on it

WildFly				Messages: 0 🛔 avinash 🗸
Home Deployments	Configuration	Runtime	Access Control	Patching
Configuration	Sub	system (31)		
Subsystems	> jo			 Subsystems A set of subsystem configurations. A subsystem is an added set of canabilities added to the core-server by
Interfaces	Da	tasources	,	an extension. A subsystem provides servlet handling capabilities; a subsystem provides an EJB container; a subsystem provides JTA, etc. A profile is a named list of subsystems, along with the details of each
Socket Binding	Re	iource Adapters		subsystem's consignations. A provise with a single number or subsystem's results in a server with a large set of capabilities. A profile with a small, focused set of subsystems will have fewer capabilities but a smaller footprint.
Paths	Ma	4		
lystem Properties	Tra	nsactions		
	EJB	3		
	EE			
	JPA			
	110	Р		
	Ba	tch		
	10			
1000 Deal				a Tools & Setting

Figure 4: Subsystem Email

- Click add and input the following information:
 - Name*: Gmail
 - JNDI: java:/jboss/mail/gmail
- Click save
- There after View the new configuration and Add a new type
 - Socket-binding: mail-smtp
 - Type: smtp
 - Username: "Your@gmail account"
 - Password: "Gmail password"
 - SSL: enable
- There after reload the server
- After reloading navigate to configurations tab and the Socket Bindings

SOCKET BINDINGS					
	Socket Bindings:	Group standard	-sockets		
Socket Binding Groups	A list of socket configuratio	ns. These configurations a	are referenced throughout the overall server/domain configuration.		
Inbound]			Add Remove	
Outbound Remote	A N	ame	Port	MCast Port	
Outbound Local	ајр		\${jboss.ajp.port:8009}		
	http		\${jboss.http.port:8080}		
	https		\${jboss.https.port:8443}		
	iiop		3528		
	liop-ssl		3529		
	management-http		\${jboss.management.http.port:9990}		
	management-https		\${jboss.management.https.port:9993}		
	txn-recovery-environmer	t	4712		
				< 1-8 of 9 > >>	

Figure 5: Socket Bindings

- Click on View and there after under standard-sockets click view
- Navigate to Outbound Remote and edit the mail-smtp socket bindings
 - Host: smpt.gmail.com

- Port: 465

			Need Help?
	🗷 Edit		
I≡ Socket Binding Groups	Name *:	mail-smtp	
Inbound			
Outbound Remote	Host *:	smtp.gmail.com	
Outbound Local	Port*:	465	
	Source Interface *:		
	Source Port *:	0	
	Fixed Source Port?*:		
	Required fields are marked v	with an asterisk (*).	
			Cancel Save

Figure 6: Outbound Socket Configuration

• Reload server

3.3.1 Deploying to WildFly

To deploy the HyperPerform system to the application you will need to build the system using from the source code.

- Ensure the WildFly server is running.
- Navigate to https://github.com/HyperPerform/hyper-perform-server/releases and download the newest release source code.
- Extract the source code
- Navigate to the root directory of the source code. A file named pom.xml should be clearly visible.
- Run the following command: mvn clean wildfly:deploy
- Maven will then ask you to provide your user name and password for the Wildfly Server.
- Thereafter Maven will automatically deploy the compiled code (war) to WildFly

3.3.2 Front-end Dashboard

Please notee that there is no release yet for the dashboard and there might be a few bugs, or limitations to the software. To start up the front end please ensure you have Node 6.4.0 or higher installed on your machine. Node can be found at https://nodejs.org/en/.

Please make sure that these commands execute successfully before attempting to run the system:

npm install —g gulp npm install —g bower npm install —g sass

Once that has completed with no errors do the following.

- Download the Dashboard source code from https://github.com/HyperPerform/ hyper-perform-web-application
- Navigate to the root directory of the source code

Run the following commands in terminal:

```
npm install
gulp build
gulp serve
```

The front-end system will auto launch in your default browser in order to view the data in the front-end system the Wildfly application server must be running.

4 Getting Started/Using the System

Once the front-end Dashboard is served your default browser should automatically open. In the event that it didn't, simply open the browser of your choice and navigate to the following URL: localhost:3000.

4.1 Logging In

Once the Dashboard loads you will be presented with the following screen:

	ј Ну	perPerform
Email Address input	Email	
Password input	2 Password	
	Login	Forgot password?
	3	
	Login Button	Forgot Password Butto

Figure 7: Login screen

- 1. **Email Address Input:** The input field for the email address with which an employee or manager was registered.
- 2. **Password Input:** The input field for the password with which an employee was registered or the password that was changed by "forgot password".
- 3. Login Button: Logs the user into the system, but first validates the input into the above mentioned fields.
- 4. Forgot Password Button: A button that should be pressed when a user has forgotten their password. This will bring up a window which asks for the users' email address. Once submitted a new password will be sent to you.

The default email for login is *admin@hyperperform.me* and password 1234. **Note:** This account should be removed, manually, once another admin is created using this default administrator account.

4.2 Your Dashboard

Once logged in the user will be presented with the following screen:



Figure 8: Dashboard

- 1. Integration Panels: Note the four colour-coded panels on top, each of these panels represents an integration. Each of the panels show your cumulative information for your specific integrations during the time period specified (discussed in point 4 below). These panels are click-able and will direct you to a details screen which will be discussed in the next subsection (subsection 4.3). This can also be done via the sidebar under the "Detailed" dropdown.
- 2. **Performance Score:** A view of your current performance score along with your performance indicator. The current performance indicators are:
 - Non-Performer (Score Below 2)
 - Standard Performer (Score between 2 3)
 - Standard-Plus Performer (Score between 3 4)
 - High Performer (Score between 4 5)
- 3. Graph Summary: A summary graph view of your performance for each colourcoded integration, during the months shown in the bottom of the graph.
- 4. Date Range Picker: The date picker where you can filter your score between two dates and times. This is discussed in the 4.2.1 below. The default time period used for the calculation of your PA Score is three months.



4.2.1 Filtering Your Performance Score

Figure 9: Date Picker

- 1. **Date Display:** A view of the selected dates for the start date and end date. These are directly modifiable by either typing a date of your choosing or using the calendar picker (described below).
- 2. Calendar Picker: When the button is clicked a calendar will be displayed above the modal window, allowing the selection of the date of your choice.
- 3. **Time Pick:** This gives you the ability to choose a specific time on the day of the date that has been chosen in the Calendar Picker.
- 4. Load Button: When this button is clicked it will take the date and time into consideration into the algorithms. Our system will then calculate the PA Score along with the values for each integration and display them to you within this time frame.

4.3 Detailed View

4.3.1 Graph View



Figure 10: Detailed View Graph

- 1. **Tabs:** The names for each repository on which their is a webhook for our system (and the current user has contributions). Each of these tabs are clickable. When clicked it will scroll down to that panel on the page so you do not have to search for it yourself. **Note:** These tabs are not specified for integrations without different repositories (i.e. entry/exit).
- 2. Graph Over Time: A performance chart of the users performance regarding the integration information in the panel. This is shown within the timeframe specified in the date picker.
- 3. **Panel Toolbox:** On the left of this toolbox shows information regarding the panel. in the middle it allows you to click to change to the table view of this panel (explained below). The graph view can be toggled back again by clicking the same button. On the right allows you to minimise the panel to make it easier to see the other panels on the page (you may need to double click for this to work).

4.3.2 Table View

,	hyper-	perform-server	hyper-perform-web-	-application hyper-per	rform-docume	ntation hyperperform github.io	
	hyper-	perform-serv	er			Total Commits: 3	34 🗠 🔺
2 Table To	Rows or 3		D	etailed Table 🚺			
	#	Username	Repository	Timestamp 👻	Commits	Message	Url
	1053	GitUser	hyper-perform-server	2016-10-10 21:23:12.0	2	Merge remote-tracking branch 'origin/develop' into develop	follow
	1047	GitUser	hyper-perform-server	2016-10-10 20:40:31.0	4	Changed the created by and added descriptions for javadoc	follow
	1002	GitUser	hyper-perform-server	2016-10-10 15:18:44.0	3	Added file for multimedia position PA score calculation with javadoc	follow
			Pag	ination 3 1	2 3 4	5	

Figure 11: Detailed View Graph

- 1. **Detailed Table:** A table that shows the details of the panel in the integration being viewed. In this example above, each row in the table shows one push to your git repository (specified in the panel heading).
- 2. Table Tools: On the left you are able to filter out how many results you want to show in the table at a time. On the right, there is a button that, when pressed, will show search bars for each column in the table. This allows the ability to search each column individually to filter out the results required.
- 3. **Pagination:** The pagination shows the numbers of different pages in the table where the rest of your data will be shown.

4.4 Signing Out

If you wish to logout then you merely click on the profile icon in the top right corner. Once clicked you will be presented with a small menu.



Figure 12: Signing Out

1. Sign Out Button:

- (a) For an employee When this button is pressed it will sign you out of your dashboard and you will be redirected back to the login page (Figure 7).
- (b) For a manager This button will sign you out of your employees' dashboard and redirect you to the Employee List Page (Figure 13) where you can view other employees' performance.

4.5 Managerial features

A variety of features are only made available to the manager within the organisation.

4.5.1 Managerial view

When a manager logs into the system, instead of being directed to a dashboard they will be directed to the following view.

 Employee List Forecasting User Management I User Management I User Management I User Management I Employee List Table 1 I Position I Score II Performance Claudio da Silva claudio.da.silva@live.com Multimedia 0.0 Non-performer Jason Gordon Jason gordon@gmail.com Software Developer 5.5 High performer Jason Gordon Jason gordon@gmail.com Software Developer 7.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 1 High performer Concertion 	 Employee List Forecasting User Management Mame Email Pesition Gaudio da.sitva@five.com Multimedia 0.0 Non-performer Jason Gordon Jason gordon@gmail.com Software Developer 5.5 High performer Jason Gordon Jason gordon@gmail.com Software Developer 5.5 High performer Jason Gordon Jason gordon@gmail.com Software Developer 5.5 High performer Jason Gordon Jason gordon@gmail.com Software Developer 5.7 High performer Bowing 1 to 5 of 5 entries 	(HyperPerforn	n ≡					a
Name I Email II Position II Score II Performance II Claudio da Silva claudio.da.silva@live.com Multimedia 0.0 Non-performer Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash.singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason gordon@gmail.com Software Developer 5.7 High performer Rohan Chlipa rohan.chlipa@live.com Software Developer 6.1 High performer	Name Email Position Score Performance I Claudio da Silva claudio da.silva@live.com Multimedia 0.0 Non-performer I Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash.singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Previous 1 Next Next Next	•	Employee List Forecasting	Employee List	ort To Employee Li:	st Table 1	Filter Em	Date Picker	•
Claudio da Silva claudio.da.silva@live.com Multimedia 0.0 Non-performer Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan chhipa@live.com Software Developer 6.1 High performer	Claudio da Silva claudio da silva@live.com Multimedia 0.0 Non-performer Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash.singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Previous 1 Next	k	User Management	Name	† Email	↓↑ Position	1 Score	↓ Performance ↓↑	
Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash.singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer	Jason Gordon gordz.gordon@gmail.com Software Developer 0.0 Non-performer Avinash Singh avinash singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Vervious 1 Next			Claudio da Silva	claudio.da.silva@live.com	Multimedia	0.0	Non-performer	
Avinash Singh avinash singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer	Avinash Singh avinash.singh@gmail.com Software Developer 5.5 High performer Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Vervious 1 Next			Jason Gordon	gordz.gordon@gmail.com	Software Developer		Non-performer	
Jason Gordon jason gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan chhipa@live.com Software Developer 6.1 High performer	Jason Gordon jason.gordon@gmail.com Software Developer 5.7 High performer Rohan Chhipa rohan.chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Previous 1 Next			Avinash Singh	avinash.singh@gmail.com	Software Developer	5.5	High performer	
Rohan Chhipa rohan chhipa@live.com Software Developer 6.1 High performer	Rohan Chhipa rohan chhipa@live.com Software Developer 6.1 High performer Showing 1 to 5 of 5 entries Previous 1 Next			Jason Gordon	jason.gordon@gmail.com	Software Developer	5.7	High performer	
Obvious das Electronicas	Showing 1 to 5 of 5 entries Previous 1 Next			Rohan Chhipa	rohan.chhipa@live.com	Software Developer	6.1	High performer	
Showing I to 5 of 5 entries Previous Next				Showing 1 to 5 of 5 entries				Previous 1 Next	



1. Employee List Table:

- (a) This table allows a manager to view all the current employees within the organisation. They can see all the necessary employee data such as name, email, performance score and performance classification.
- (b) A manager also has the ability to view an employees' dashboard. This can be achieved by simply clicking on the employees' name and the manager will be directed to the corresponding employees' dashboard.
- 2. Filter Employee's: This search bar allows a manager to filter the results by searching for any value in any field of the table. The resulting table will show the filtered results only.
- 3. **Date Picker:** This allows a manager to filter the scores between two dates and times resulting in a change in the table to those scores between that specific period.
- 4. Export To: Managers also have the ability to export the table to a PDF or CSV file or even directly print it out. This allows the manager to keep a copy with them at any time and can aid with record keeping by allowing them to print the

table at regular intervals. **Note:** After filtering the results (via point 2) only the filtered data will be exported and not the whole table.

4.5.2 User registration

The responsibility of adding users to the system is given to the manager. When registering a new user the manager must go through a three step registration process.

	HyperPerform	
	Step 1 / 3	
	First Name	
2	Surname	
3	Email Address	
	Next	
N	ext Step Button	

Figure 14: Registration step 1

- 1. First Name: The first name of the user being registered.
- 2. Surname: The surname of the user being registered.
- 3. Email Address: The email address with which the user being registered will login. Note: This must be a valid email address because the users password will be sent to them via email.
- 4. Next Step Button: Move from step 1 to step 2. Your input will be validated on click of this button.

HyperPerform	
Step 2 / 3	
Git Username	
2 HyperPerform Username	
3 Password Confirm Password 😦 4	
Error: Password must be at least 6 characters	
Previous Next 5 6 Previous Step Button Next Step Button	

Figure 15: Registration step 2

- 1. Git Username: This is the users' exact git username which will be used in collecting information from their GitHub account.
- 2. HyperPerform Username: A username given to the registered user.
- 3. Password: The password the user will use to login to their dashboard.
- 4. **Confirm Password:** A confirmation of the password that was typed in the above field, used for security reasons.
- 5. **Previous Step Button:** Takes you back to step one where you can edit the information.
- 6. Next Step Button: Continues to step 3. Your input is validated again on click of this button.

	O HyperPe	erform
	Step 3 / 3	
Role Drop <mark>down</mark>	1 Employee	•
Position Dropdown	2 Software Developer Previous Sign Up	•
	3 Submit all steps	

Figure 16: Registration step 3

- 1. **Role Dropdown:** A list of role types where the role of the user being registered is chosen. Currently existing roles are:
 - Administrator
 - Employee
- 2. **Position Dropdown:** A list of positions in the system where the position of the user being registered is chosen. Currently existing positions are:
 - Web Developer
 - Software Developer
 - Multimedia
- 3. **Submit all steps:** A button that submits all the fields that were input in all 3 steps. This will then send an email to the registered user which includes their login details. so that they can view their individual dashboard.

Currently existing roles are: Currently existing positions are:

- Web Developer
- Software Developer
- Multimedia

4.5.3 Forecasting

The forecasting section allows for an administrator to add forecast values to the system. A forecast value is a prediction made by an administrator with regards to employee performance.

=			Add Integration ①	+
GitCommits Forecast details			Panel Toolbox 🗿 🗸	××
Integration Panel (2)		Add/Rei	move Forecast ③ 🗕	+
Position				
Web Developer	•	20	Week	•
Software Developer	•	20	Week	•
Multimedia	Ŧ	10	Week	•
			✓Up	late
GitIssues Forecast details				××
			_	+
Position		Value	Time	
Web Developer	•	5	Week	•
Software Developer	•	5	Week	•
Multimedia	•	0	Week	•

Figure 17: Dashboard errors

- 1. Add Integration: New integrations can also easily be added. Simply click on the + on the navbar to bring up a modal (Figure ?). On this modal a new integration can be added to the system. Note: when adding a new integration, at least one position and forecast value must be added.
- 2. Integration Panel: Each integration is displayed to the administrator in its own panel. Each panel consists of a table which shows each position along with its corresponding forecast value. All the values in the table are editable; this allows for different employee positions to have different forecast values in the same integration.

3. Add/Remove Forecast:

(a) If the administrator does not wish to directly modify the table then simply click on '+' button to add a new row to the forecast table.

- (b) If you want to remove a forecast from the table simply click the '-' button and it will remove a single row at a time.
- (c) **Note:** you will not be able to add more rows in the table than there are positions in the position dropdown. Also you will not be able to remove all rows in a table, there must be at least 1 at all times.
- 4. Panel Toolbox: This toolbox allows you to do the following:
 - (a) Minimise the panel with the \wedge button so that you can see the rest of the integrations more clearly.
 - (b) Delete the current integration with the 'x' button. When this is pressed a confirmation box will be shown to make sure that you want to delete the integration.

4.6 Errors

The dashboard provides error messages in the event there's an issue.

			Failed to load ②
≡	No Data	I	Failed to load PA Score *
GitHub	Travis	Issues	Failed to load PA Score ×
Total Commits	Build Ratio	A Issue Ratio	Unable to connect to the server * From: Summary 3 Unable to connect
OVERVIEW			

Figure 18: Dashboard errors

- 1. No Data: These icons in place of the values indicates that the data from the server was unable to be received by our dashboard. The reasons why are shown on the top right of the screen (also discussed below).
- 2. Failed to load: This indicates that the dashboard was unable to load the PA score due to an error. This is most likely that either you are not connected to the internet or that you have input an invalid date or time in the date picker.
- 3. Unable to connect: This error is due to the fact that you are most likely not connected to the internet or there is an issue on our side.

≡	Unable to connect to the server From: GitHub
An error occurred	
	Server Error

Figure 19: Server connection error

1. Server Error: If the system is not connected to the internet no data can be requested from the server.

	▲ No commits found
No results found	No Data Found



1. No Data Found: If a new integration has been added to the system and no data has been collected from that particular integration, then the user will see this error message.